

Batch FTPZIP - Massive - Settings.xml

Overview

Settings.xml is the only mandatory content of the ZIP Archive.

The XML structure is divided in three main nodes:

- **Header:** General data regarding FTPZIP operations
- **Content:** Data about the Mailing that will be executed and the Newsletter that will be created.
- **AdvancedSettings:** Data about message creation, Kind of Mailing, CSV File features.

Follow an example of all nodes includes in settings XML

```
Settings.xml all nodes

<?xml version="1.0" encoding="UTF-8"?>
<FtpZip>
  <Header>
    <ActionType>full</ActionType>
    <CampaignCode>Campaign0009</CampaignCode>
    <FormatVersion>0.1</FormatVersion>
    <NotifyEmail>peter@example.com</NotifyEmail>
  </Header>
  <Content>
    <ListId>1</ListId>
    <ListGUID>08c6348c-1e6b-4ae7-b44c-156fc4a7f012</ListGUID>
    <SenderName>John Doe</SenderName>
    <SenderEmail>john@doe.com</SenderEmail>
    <ReplyToEmail>jane@doe.com</ReplyToEmail>
    <EmailSubject>Campaign0009</EmailSubject>
    <ScheduleDateTime>2014-11-04T11:20:00.000</ScheduleDateTime>
    <Notes>Notes for campaign 00009</Notes>
  </Content>
  <AdvancedSettings>
    <Separator>;</Separator>
    <Attachments>>false</Attachments>
    <DynamicFields>>true</DynamicFields>
    <EmbeddedImages>>false</EmbeddedImages>
    <LinkTracking>>true</LinkTracking>
    <HttpLinkTracking>>true</HttpLinkTracking>
    <HttpsLinkTracking>>true</HttpsLinkTracking>
    <MailToTracking>>false</MailToTracking>
    <FtpTracking>>true</FtpTracking>
    <NewsTracking>>true</NewsTracking>
    <QueryStringAdditionalParams></QueryStringAdditionalParams>
    <ContentOverride>
      <MessageId>1136</MessageId>
      <CloneMessage>>true</CloneMessage>
    </ContentOverride>
  </AdvancedSettings>
</FtpZip>
```

Input fields detail

Following meanings of each node of **settings.xml** divided by main node.

Node <Header>

| Name | Type | Requires value? | Sample values | Meaning | Notes |
|------|------|-----------------|---------------|---------|-------|
|------|------|-----------------|---------------|---------|-------|

| | | | | | |
|---------------|--------|---|--|--|---|
| ActionType | string | Y | One between "save", "full" or "send" | The kind of action FTPZIP will take with regard to the submitted ZIP archive. When set to save, FTPZIP will only create an email message without importing any recipient or scheduling any mailings. | ActionType is a very important field as its value drives a big shift in the executed tasks. |
| CampaignCode | string | Y | Any | This is a unique identifier for the campaign. FTPZIP will read this value at each session to prevent users from uploading the same campaign twice by mistake. | |
| FormatVersion | string | Y | < 0.1 0.2 > | This value indicates the kind of xml validation FTPZIP will run. Current implemented format is 0.1, and it will run xml validation against its xsd schema definition file. | |
| NotifyEmail | String | N | peter@example.com | An email report containing the process result (success/failure) is sent to the specified address. | Recommended, it is the only way to receive an automated notification in case of errors |

Node <Content>

| Name | Type | Requires value? | Sample values | Meaning | Notes |
|------------------|--------|-----------------|--|---|--|
| ListId | int | Y | < 1 2 3 > | The numeric identifier for the List in the MailUp account in which the various tasks will be executed (creation of the message, import of recipients, etc.). This is unique within a MailUp account, but not across MailUp accounts. | To locate your lists id's please see: http://help.mailup.com/display/mailupapi/Codes+Table+and+List+GUID |
| ListGUID | String | Y | b947d468-2751-40a7-83bf-1ecca0bbd6a1 | The unique identifier for each List across all MailUp accounts. ListID and ListGUID must refer to the same List. | To locate your lists Guid's, please see: http://help.mailup.com/display/mailupapi/Codes+Table+and+List+GUID |
| SenderName | String | N | | The display name for the sender in the campaign being created /sent | If empty, the default value for the List will be used. |
| SenderEmail | String | N | | The email address that the campaign will be sent from | If empty, the default value for the List will be used. Mind that this is not an arbitrary field, the sender Email has to be approved with your admin account to prevent any kind spam like activities. |
| ReplyToEmail | String | N | example@email.com | The email address used when the subscriber reply to the received campaign. | If empty, the default value for the List will be used. |
| EmailSubject | String | N | | The email message subject | |
| Notes | String | N | This is a note | The email message note | |
| ScheduleDateTime | String | N | | The date/time at which the campaign will be sent. If time is too close to current time, or already in past, or left empty, campaign will be sent out immediately. <u>The date/time have to be written using the ISO 8601 format.</u> The time zone mailing will occur for must to be specified in the ScheduleDateTime value as foreseen for the ISO 8601 format. (see https://www.w3.org/TR/NOTE-datetime) | If you upload many ZIP files with the same scheduled date and time, mailing will run in parallel. If you upload many ZIP files without a scheduled date, mailing will run sequentially, according to the file detection order. If the scheduled date and time is earlier than the actual processing time, the scheduled date&time will be ignored and mailing will be sequential. if time zone isn't specified it will be used western European standard time zone as default. (GMT+ 1) |

Node <AdvancedSettings>

| Name | Type | Requires value? | Sample values | Meaning | Notes |
|------|------|-----------------|---------------|---------|-------|
|------|------|-----------------|---------------|---------|-------|

| | | | | | |
|-------------------------------|---------------|---|--|---|---|
| Separator | String | Y if ActionType set to Full, N if set to Newsletter | ; | The column delimiter used in the Recipients.csv file. | |
| Attachments | Bool (string) | Y | < true false > | Attach files to current mailer campaign | If set to true FTPZIP will expect the folder <i>attachments</i> to be included in the submitted ZIP archive |
| DynamicFields | Bool (string) | Y | < true false > | Toggles dynamic fields | |
| Embedded Images | Bool (string) | Y | < true false > | Toggles use of embedded images | |
| LinkTracking | Bool (string) | Y | < true false > | Toggles link tracking | |
| HttpLinkTracking | Bool (string) | Y | < true false > | Toggles plain http link tracking | |
| HttpsLinkTracking | Bool (string) | Y | < true false > | Toggles https link tracking | |
| MailToTracking | Bool (string) | Y | < true false > | Toggles Mailto tracking | |
| FtpTracking | Bool (string) | Y | < true false > | Toggles FTP tracking | |
| NewsTracking | Bool (string) | Y | < true false > | Toggles News Tracking | |
| QueryStringAdditionalParams | String | N | utm_medium=email&utm_campaign=Nov14+offers | Appends a querystring to all included links | Suitable for third party campaign tracking systems such as Google Analytics |
| PreHeader | String | N | This is a preheader | String that will be added to the email message head as preheader. | |
| ContentOverride /MessageID | Int | N | 25 | MessageID is the newsletterID to be used for the outgoing campaigns; it will be taken into consideration only for ActionType "send" | Suitable when you send the same message repeatedly and don't need to create each time a fresh new one. |
| ContentOverride /CloneMessage | Bool (string) | N | < true false > | Create a copy of the newsletter described in MessageID Fields. The copy will be sent. | Suitable when you send the same message repeatedly but want to see separated statistics in the MailUp Web Application.. |